

Article

Not peer-reviewed version

Exploring the Potential of Heteroatom-Doped Graphene Nanoribbons as a Catalyst for Oxygen Reduction

Eduardo S Cardoso, Guilherme V Fortunato, Clauber D Rodrigues, Marcos R Lanza, GILBERTO MAIA

Posted Date: 8 August 2023

doi: 10.20944/preprints202308.0673.v1

Keywords: Oxygen-reduction reaction; hydrogen peroxide production; graphene nanoribbon; heteroatom-doping; functional groups



Preprints.org is a free multidiscipline platform providing preprint service that is dedicated to making early versions of research outputs permanently available and citable. Preprints posted at Preprints.org appear in Web of Science, Crossref, Google Scholar, Scilit, Europe PMC.

Copyright: This is an open access article distributed under the Creative Commons Attribution License which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Disclaimer/Publisher's Note: The statements, opinions, and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions, or products referred to in the content.

Article

Exploring the Potential of Heteroatom-Doped Graphene Nanoribbons as a Catalyst for Oxygen Reduction

Eduardo S. F. Cardoso ¹, Guilherme V. Fortunato ², Clauber D. Rodrigues ³, Marcos R. V. Lanza ² and Gilberto Maia ^{1,*}

- Institute of Chemistry, Federal University of Mato Grosso do Sul, Av. Senador Filinto Muller 1555, Campo Grande 79074-460, MS, Brazil; eduardosafreca@gmail.com
- ² São Carlos Institute of Chemistry, University of São Paulo, Avenida Trabalhador São-Carlense 400, São Carlos 13566-590, SP, Brazil; g.fortunato@usp.br (G.V.F.); marcoslanza@usp.br (M.R.V.L.)
- ³ State University of Mato Grosso do Sul; Rua Rogério Luis Rodrigues s/n, Glória de Dourados 79730-000, MS, Brazil
- * Correspondence: gilberto.maia@ufms.br; Tel: +55-67-3345-3596

Abstract: In this study, we created a series of N, S, and P-doped and co-doped carbon catalysts using a single graphene nanoribbon (GNR) matrix and thoroughly evaluated the impact of doping on ORR activity and selectivity in acidic, neutral, and alkaline conditions. The results obtained showed no significant changes in the GNR structure after the doping process, though changes were observed in the surface chemistry in view of the heteroatom insertion and oxygen depletion. Of all the dopants investigated, nitrogen (mainly in the form of pyrrolic-N and graphitic-N) was the most easily inserted and detected in the carbon matrix. The electrochemical analyses conducted showed that doping impacted the performance of the catalyst in ORR through changes in the chemical composition of the catalyst, as well as in the double-layer capacitance and electrochemically accessible surface area. In terms of selectivity, GNR doped with phosphorus and sulfur favored the 2e- ORR pathway, while nitrogen favored the 4e- ORR pathway. These findings can provide useful insights into the design of more efficient and versatile catalytic materials for ORR in different electrolyte solutions, based on functionalized carbon.

Keywords: oxygen-reduction reaction; hydrogen peroxide production; graphene nanoribbon; heteroatom-doping; functional groups.

1. Introduction

Graphene is a single-layer, 2D material made of carbon atoms under a crystalline arrangement [1]; owing to its large surface area and ease of functionalization through heteroatom-doping, this carbon material is extremely valued for application in chemical reactions. In addition, its low density, high conductivity, chemical stability, and resistance to corrosion make graphene an efficient, durable material for catalytic applications [1–3].

Graphene comes in a variety of forms, and each form is distinctively characterized by its peculiar structural, electrical, and optical properties. Graphene nanoribbons (GNR) are a special class of graphene which has gained traction among researchers; GNR have been widely applied in catalytic reactions/processes due to their unique physical-chemical properties [4]. GNR are thin strips of graphene – measuring just a few nanometers wide (commonly described as 1D material), which can exhibit a metallic or semi-conductor characteristic depending on their width and edge structure [2,4,5]. The suitable properties of GNR make them useful for application in electronics, sensing devices, and energy storage [2,4]. GNR can be synthesized through a wide range of methods including chemical vapor deposition [2], patterning with lithography techniques [6], or through chemical oxidation of carbon nanotubes [5,7]. GNR have been successfully applied alone or in combination with other materials in different electrolyte solutions to catalyze several electrochemical reactions including water splitting [8], CO₂ reduction reaction [9,10], and oxygen reduction reaction

(ORR) [7,11–13]. Incorporating heteroatoms like nitrogen, sulfur, or oxygen into carbon materials - a mechanism referred to as doping, provides us with considerable benefits, as it leads to the development of carbon materials with suitable properties that are highly efficient for catalytic applications [14,15]. Doping alters the electronic structure of the carbon material, and this can effectively boost its ORR catalytic activity in acidic, neutral, and alkaline media. For instance, incorporating nitrogen into graphene leads to the development of pyridinic nitrogen - a material with high electron density, which increases the catalytic activity of graphene in ORR, particularly in alkaline environments [15]. Similarly, adding sulfur or oxygen to graphene creates defects or dopants, which enhance the catalytic activity and selectivity of the material [15–17]. However, the ORR activity and selectivity exhibited by heteroatom-doped carbon catalysts can undergo dramatic variations depending on the pH of the electrolyte [18], yet these phenomena remain inadequately understood. Certain doped carbon materials showcase heightened activity in either acidic or alkaline conditions, while others demonstrate remarkable performance across a broad pH range [18-22]. These differences can be attributed to divergent behaviors of the reactants (i.e., protons or hydroxide ions and their availabilities) and intermediates. Furthermore, heteroatom-doped carbon catalysts may present a multitude of enriched reversible redox couples on their surfaces, serving as conduits for charge transfer to adsorbed oxygen [19]. The electrochemical activity or inactivity of these redox couples toward the ORR is contingent upon the specific electrolyte employed [19]. Doping may also help improve the stability and durability of carbon materials, as is the case of nitrogen-doped carbon materials which exhibit greater resistance to oxidative degradation and longer lifetime when applied in catalytic reactions/processes [23].

Recently, considerable attention has been devoted toward creating nitrogen, oxygen, sulfur, and phosphorus-doped graphene structures targeted at enhancing the electrocatalytic performance of the carbon materials, especially in ORR processes. Regarding the development of ORR electrocatalytic materials, although a plethora of studies have been reported in the literature, the study conducted by Xiang et al. [24] appears to be outstanding. Xiang et al. [24] found that N-doped GNR, produced through the oxidative unzipping of CNTs and N-doping with urea, and its abundant edges have a synergistic effect on the ORR process through the 4-electron pathway; these authors also pointed out that pyridinic and graphitic-N are the main contributors when it comes to catalyzing the ORR process. Based on the application of the hard-templating method, Dong et al. [25] produced porous graphene foam doped with B, N, and P, which effectively enhanced ORR performance in comparison with graphene foam doped with single or dual-elements. Han and Chen [26] showed that keeping the N proportion more than twice higher than the proportion of P in graphene co-doped with P and N (G-PN₃) improved the catalytic activity in ORR and selectivity under the 4 electron mechanism. Zhao et al. [27] found that doping ordered mesoporous carbon (OMC) first with P and later with N led to an increase in the graphitic-N ratio and improved the catalytic activity in ORR. Yang et al. [28] developed and applied edge-rich graphene nanoribbon co-doped with N and S via thermal annealing in ORR which led to significant improvements in catalytic activity. Wang et al. [29] used a 3-D structured carbon nanotube/GNR co-doped with N and S from the thermal treatment of thiourea which effectively catalyzed a 4-electron ORR process. Kan et al. [30] synthesized carbon nanospheres doped with N and N and S (NCSs and NSCSs) through melanosome pyrolysis with NSCS; the application of these carbon-doped material resulted in better catalytic activity in ORR aimed at water production. Li et al. [31] synthesized 3-D reduced graphene oxide co-doped with N and S(NS-3DrGO) through pyrolysis; the application of this material resulted in better ORR activity with the successful transfer of 4 electrons. Zhai et al. [32] produced graphene oxide doped with S by using DMSO as solvent and S precursor and the application of the solvothermal method; the authors successfully applied the S-RGO in ORR with good results. Yazdi et al. [33] produced helical CNx-GNRs co-doped with N and S (CNx/CSx-GNRs) through annealing, where the application of the material resulted in efficient ORR activity and 4-electron selectivity. The authors of the aforementioned study attributed the efficient ORR activity to the synergistic effects derived from the co-doping of nitrogen/sulfur and to the helical unzipping mechanism which gave rise to graphene nanoribbons with multifaceted structure; according to the authors, the S co-doping mechanism led to an increase in pyridinic-N

groups in the GNR structure - these groups constitute the main active sites which helped enhance ORR activity on the edges [33]. In another related study, through annealing, Wang et al. [34] synthesized a co-doped N and P 3-D structured GNR/CNT composite through annealing; the application of the synthesized material as ORR catalyst resulted in a satisfactory performance. Tammeveski and co-workers [35] employed both wet and dry ball-milling methods to produce sulphur and nitrogen co-doped graphene-based catalysts. These catalysts exhibited a significant presence of pyridinic N in both cases, with the catalysts produced by dry ball-milling being more suitable for facilitating a complete 4e- oxygen reduction. Additionally, they synthesized silicon carbide-derived carbon (SiCDC) doped with nitrogen and phosphorus moieties using a ball-milling method, which improved the 4e- ORR pathway by incorporating active sites derived from the nitrogen and phosphorus moieties [36]. Furthermore, they successfully synthesized N,P-doped SiCDC and CNT with hierarchical pore structures via a ball-milling method, leading to further improvements in the 4e- ORR pathway [37]. Dey and co-workers [38] synthesized a triazine-based covalent organic polymer (Trz-COP) metal-free electrocatalyst with dual-active sites. They also employed a polymer-assisted electrophoretic exfoliation method on graphite to produce graphenepolypyrrole (G-PPy) in dilute acidic medium, followed by a high-temperature treatment to incorporate N atoms into the graphene matrix. This resulted in the formation of an N-doped graphene-PPy (NG-PPy) metal-free catalyst [39]. Additionally, they synthesized a bis(terpyridine) (hexadentate chelating ligand) with Fe, promoting the formation of FeN_x/C active sites (Fe-N/C_(H,P) electrocatalyst) [40]. These catalysts demonstrated efficient ORR electrocatalysis, predominantly resulting in the production of water.

Based on the above considerations, it is clear that doping carbon materials with heteroatoms, such as nitrogen, sulfur, oxygen, and phosphorus, leads to the development of carbon materials with suitable properties that have great potential for catalytic applications; strangely though, this technique has still not been fully explored in the literature, especially considering the specific benefits that can be derived from the doping mechanism, depending on the heteroatom, medium, and type of reaction involved. Finding an electrocatalyst that can efficiently produce water or hydrogen peroxide through oxygen reduction reaction (ORR) in different electrolyte solutions remains a daunting challenge today. In the present work, we developed and characterized a series of N, S, and P-doped and co-doped carbon catalysts using the same GNR matrix and thoroughly evaluated the impact of doping on the catalytic activity in ORR and selectivity under acidic, neutral, and alkaline conditions using the rotating ring-disk electrode (RRDE) technique. The results obtained from the characterization of the proposed materials showed that the heteroatom doping process did not significantly alter the GNR structure, though it altered the surface chemistry which was caused by the insertion of the heteroatoms and oxygen depletion. Among the dopants investigated in this study, N was the most easily inserted and detected in the carbon matrix. The electrochemical analyses conducted revealed that heteroatom doping or co-doping and residual oxygen levels influenced the physicochemical properties of the catalyst, as well as the ORR activity and selectivity, which varied with changes in the electrolyte solution. The study provides significant insights to readers in the relevant field, including: 1) the matrix (GNR) used for doping demonstrates limited ORR electrocatalytic performance, 2) the soft doping procedure employed does not substantially alter the matrix. Consequently, this enables a thorough investigation of the doping effects on ORR activity and selectivity in various electrolyte solutions.

2. Experimental Part

2.1. Reagents and Instruments

The chemical compounds used for the experiments were as follows: phosphorus pentoxide (P₂O₅, 99 %), potassium persulfate (K₂S₂O₈, 99 % purity), hydrogen peroxide (H₂O₂, 30 %), - all were acquired from Vetec (Duque de Caxias, RJ, Brazil). Potassium permanganate (KMnO4, 98 %) was acquired from Nuclear (Diadema, SP, Brazil). Potassium sulfate (K₂SO₄, 99%) was obtained from Proquimios (Rio de Janeiro, RJ, Brazil). Sodium nitrate (NaNO₃), hydrochloric acid (HCl), potassium hydroxide (KOH) and sulfuric acid (H₂SO₄, 98%) were obtained from Merck (Darmstadt, Germany).

Ammonia hydroxide (NH₄OH) solution (28 wt% in H₂O), hydrazine sulfate (NH₂NH₂.H₂SO₄, 99%), and multi-walled carbon nanotubes (\geq 98 % purity, containing 6–8 tube walls) were purchased from Aldrich (Saint Louis, MO, USA). The water used for the preparation of all solutions was obtained from the Gehaka reverse osmose equipment, with resistivity above 18 M Ω cm and temperature of 25 °C.

A three-electrode glass electrochemical cell was used for the experiments; the cell was composed of a carbon paper HCP030N (geometric area of $3.5~\rm cm^2$) which was used as counter electrode, a reversible hydrogen electrode which was used as reference electrode, and Teflon-embedded glassy carbon (GC) disk/Pt ring rotating electrode which was used as working electrode (the disk and ring had geometric area of $0.196~\rm cm^2$ and $0.11~\rm cm^2$, respectively, with a collection efficiency of N=0.26 – this information was obtained from the manufacturer - Pine Research Instrumentation).

2.2. Electrode Preparation

The RRDE (GC disk/Pt ring) electrode was polished with alumina paste (1 μ m) and cleaned by sonication, alternating in ultrapure water (Gehaka, resistivity > 18 M Ω cm), isopropyl alcohol, and 0.1 M HClO₄ (Tedia, suprapure quality) for 5 minutes in each solvent. The GC disk was subjected to 12 scanning cycles at a sweep rate of 50 mVs⁻¹ in the potential range of 0.05 - 1.2 V. The Pt ring was also subjected to 300 scanning cycles at 900 mVs⁻¹ in the potential range of 0.05 -1.2 V. Both cycling experiments were performed in 0.1 M HClO₄ solution saturated with N₂ (acquired from White Martins, 4.0 of purity); subsequently, the GC disk/Pt ring was washed with ultrapure water and dried with N₂ flow. A loading of 150 μ g cm⁻² of undoped or doped GNR on the GC disk surface was obtained by dripping 30 μ L of 1.0 mg mL⁻¹ aqueous solution of undoped or doped GNR on the disk surface, which was then dried at room temperature.

2.3. Apparatuses, Measurements, and Material Characterization

To perform hydrodynamic linear potential (HLS) and cyclic voltammetry (CV) scanning analyses, a bipotentiostat AFP2 WaveDriver 20 – galvanostat (Pine Research Instrumentation) was used – the equipment was connected to AFMSRCE speed modulated rotator.

A PGSTAT128N potentiostat-galvanostat (Autolab) equipped with the FRA2.X module was used during the electrochemical impedance spectroscopy (EIS) experiments. EIS measurements were performed at an open circuit potential with average values of 0.72, 0.89 and 0.82, while the working electrode was placed in the presence of 0.5 M H₂SO₄, 0.1 M K₂SO₄, and 0.1 M KOH solutions, respectively, in the frequency range of 10 mHz to 100 kHz, with disturbance potential of 10 mV (rms). The ohmic drop resistance, adjusted from a high frequency EIS intercept, was used to correct each HLS curve. The measured ohmic drop resistances were on average 5.2, 36.8, and 38.5 Ω in 0.5 M H₂SO₄, 0.1 M K₂SO₄ and 0.1 M KOH solutions, respectively.

The Fourier transform infrared spectroscopy measurements were carried out using Bomen Fourier transform infrared spectrophotometer with a spectral window of 400 to 4000 cm $^{-1}$. The catalyst samples were produced by grinding the dried catalyst powder (approximately 30 μ g) with potassium bromide (approximately 35 mg) in a mortar until a fine and homogeneous powder was obtained. After pressing the powder, a translucent tablet was formed.

The Raman spectra were obtained at room temperature using LabRam HR Evolution micro-Raman spectrometer from Horiba Jobin-Yvon, a solid-state laser operating at 633 nm, a standard grating (600gr/mm), and EMCCD detector (Synapse EM). To avoid overheating and the occurrence of photochemical phenomena, the samples were excited with low intensity laser (ca. 2 mW). The laser was focused on the sample using a 100 objective (Olympus, MPlan N). The spectra were collected over the course of 12 seconds.

Elemental analysis (EA) was performed using a Scientific Flash 2000 CNHS/O Elemental Analyzer Thermo Equipment under cycle operating conditions (run time) of 720 s and oven temperature of 950°C for CHNS determinations and under the cycle (run time) of 400 s and oven temperature of 1060°C for O determination.

5

The catalyst nanostructures were characterized by TEM using JEM 2100F (JEOL) or Philips CM200, both operating at 200kV. The XPS analyses were performed using the PHI Quantera II surface analysis equipment. The Al K α line (1486.6 eV) was used as the ionization source, operating at 15 kV and 25 W. After performing the background subtraction, the spectra were deconvoluted using a combination of Lorentzian (30%) and Gaussian Voigt (70%) functions.

Thermogravimetric analyses were conducted using Shimadzu TGA-50 thermogravimetric analyzer, with FID Synthetic Air 5.0 gas flow of 50 mL min⁻¹, in temperatures ranging from ambient to 900 °C and a heating rate of 10 °C min⁻¹; the samples were placed in alumina ceramic crucibles.

2.4. GNR Synthesis and Syntheses of Different Doped GNR Samples

The synthesis of graphene nanoribbons (GNR) derived from the chemical oxidation of multiwalled carbon nanotubes (MWCNTs) was carried out utilizing the method previously described elsewhere [7]. Briefly, MWCNTs were dispersed in concentrated H2SO4 solution containing K2S2O8 and P2O5 and then heated (with stirring) at 80 °C for 6 h. The resulting solution was diluted in water at 0 °C and filtered through a 0.22 µm nylon membrane and finally washed with plenty of high purity water. This pre-oxidized material was re-oxidized in a concentrated H2SO4 solution containing NaNO3 and KMNO4 at 30°C during 2 h, then diluted in high purity water, and then H2O2 (30% solution) was added and again diluted with water. After 24 h, this dispersion was centrifuged and washed with HCl and water (10:90) resulting in graphene oxide nanoribbons (GONRs). The GONRs were immersed in hydrazine sulfate and NH3OH solution under vigorous stirring, followed by heating to 95 °C during 2 h. After reaching room temperature, the dispersion was filtered initially with a 5% NH₃OH solution, washed well with enough high purity water, finally producing the GNRs.

The doping of GNR with N and/or S and/or P was performed using NH₄OH and/or N₂H₆SO₄ and/or K2S2Os and/or P2O5; the doping was carried out in two hydrothermal synthesis steps. The first step was executed as summarized in Table 1. This step involved mixing 0.02g GNR with defined amounts of the dopant or dopants (NH₄OH and/or N₂H₆SO₄ and/or K₂S₂O₈ and/or P₂O₅) and pouring water in a 30 mL beaker; this was followed by heating and constant stirring for 3 hours, and finally washing/centrifugation several times.

Table 1. Summary of the first and second steps of the synthesis.

Catalyst	First step Involved Heat Treatment at 95°C for 3h (Component Amounts as Shown Below), Followed by 10 Cycles of Washing/Centrifugation (7,000 rpm) with Water Replacement.						Second Step Was Executed in Autoclave System for 12 h at 150°C (Component Amounts as Shown Below), Followed by 10 Cycles of Washing/Centrifugation (7,000 rpm) with Water Replacement; Subsequently, the Material Was Dried at 60°C for 24 h				
	GNR	$K_2S_2O_8$	P ₂ O ₅	NH ₄ OH	N ₂ H ₆ SO ₄	H_2O	V ₂ S ₂ O ₂ (α)	P ₂ O ₂ (α)	NH ₄ OH	H ₂ O	
	(g)	(g)	(g)	(mL)	(g)	(mL)	$K_2S_2O_8(g)$	P ₂ O ₅ (g)	(mL)	(mL)	
GNRN	0.02	-	-	1	1.06	30	-	-	30	-	
GNRS	0.02	0.2	-	-	-	30	0.2	-	-	30	
GNRP	0.02	-	0.2	-	-	30	-	0.2	-	30	
GNRNS	0.02	0.2	-	1	1.06	30	0.2	-	30	-	
GNRNP	0.02	-	0.2	1	1.06	30	-	0.2	30	-	
GNRSP	0.02	0.2	0.2	-	-	30	0.2	0.2	-	30	
GNRNSP	0.02	0.2	0.2	1	1.06	30	0.2	0.2	30	-	

In the second step of synthesis, the product of step 1 was mixed with 30 mL of water or NH₄OH, together with the respective amount of dopant or dopants (Table 1) and subjected to constant magnetic stirring until complete dispersion was obtained. The resulting solution was heated in an autoclave system at 150°C for 12 h. The final products were washed by centrifuging using ultrapure H₂O and dried at 60°C for 24 h (Figure 1).

6

GNR* = product resulting from first step

Figure 1. Scheme illustrating the modification of GNR to produce GNRN, GNRS, GNRP, GNRNS, GNRNP, GNRNSP, and GNRNSP.

3. Results and Discussion

3.1. FT-IR and Raman Study

Initially, Fourier Transform infrared spectroscopy (FT-IR) was used to monitor characteristic vibrations; this was done in order to assess any possible changes in the functional groups present on the graphene surface after the doping process. Figure 2a shows the FT-IR spectra for the different doped and undoped GNR, $K_2S_2O_8$, and P_2O_5 materials.


In general, FT-IR responses for the different doped and undoped GNR materials show peaks related to OH stretching vibration from water, ring stretching, in-plane C-H bending strongly mixed with C—C vibrations or C-N stretching, ring bending vibration or C-P stretching or C—S stretching, out-of-plane ring bending, and C-S stretching [41,42] (Table S1). However, when GNR is doped with nitrogen (GNRN), the ring stretching peak is displaced to a higher wavenumber simultaneously and the C-N stretching is observed at a higher wavenumber as a broad peak (1,203 cm⁻¹); the ring bending vibration observed in the GNRN is also slightly displaced to a lower wavenumber and the catalyst also exhibits an out-of-plane ring bending strong peak in comparison with the GNR (Figure 2a and Table S1).

When GNR is doped with sulfur (GNRS), the ring stretching peaks are evidenced by the presence of three strong peaks at 1,693, 1,637, and 1,527 cm⁻¹; simultaneously, the C-S stretching is observed as a broad small peak at 1,086 and a weak peak at 669 cm⁻¹ in comparison with the response obtained for the bare GNR (Figure 2a and Table S1) - evidencing the doping of the GNR matrix with S atoms.

When GNR is doped with phosphorous (GNRP), the ring stretching peaks are evidenced by the presence of three well-defined peaks at 1,693, 1,637, and 1,530 cm⁻¹; simultaneously, the C-P stretching is observed as a broad strong peak at 1,038 cm⁻¹ in comparison with the response obtained for the bare GNR (Figure 2a and Table S1).

The ring stretching peaks for GNR doped with nitrogen and sulfur (GNRNS), nitrogen and phosphorous (GNRNP), sulfur and phosphorous (GNRSP), and nitrogen, sulfur, and phosphorous (GNRNSP) can be found to be similarly identical (defined peaks at around 1,693, 1,640, and 1,525 cm⁻¹); simultaneously, the C-S stretching is observed as a weak peak at 669 cm⁻¹ for those GNR doped with sulfur and the other elements. The GNR doped with nitrogen and the other elements exhibits a broad strong peak at around 1,090 cm⁻¹, which is most probably related to the stretching of C and the other elements, while the GNR doped with sulfur and phosphorous (GNRSP) exhibits a broad weak peak at around 1,068 cm⁻¹, which is most probably related to the stretching of C and the other elements (Figure 2a and Table S1). These results help to confirm the doping of GNR with their respective doping elements.

Figure 2b shows the Raman spectra obtained for GNR and the doped GNR samples.






Figure 2. a) FT-IR spectra for different samples of doped and undoped GNR, K₂S₂O₈, and P₂O₅. b) Raman spectra for the undoped and doped GNR samples.

Clearly, one can observe the intense first-order D band (disorder band) at ≅1328 cm⁻¹ and G band (graphite band) at $\cong 1597 \text{cm}^{-1} [5,43-46]$ (Table S2). The higher intensity of the D band in comparison with the G band (ID/IG ratio, Table S2) is attributed to the contribution of the bands as defects [44]. Also, the double-resonant signals assigned to 2D[47], D+D'[47], and 2D' bands at ≅2651, 2914, and 3214 cm⁻¹, respectively, are found to be visible though with lower intensity [44,48–50] (Table S2). The D+D' and 2D' bands observed in the Raman spectra are related to disorder-induced and second-order Raman overtone of damaged graphene [51]. The displacement of these bands to higher wavelengths suggests a higher degree of disorder in the doped GNR in comparison with undoped GNR (as shown in Table S2). Some GNR multilayers present in the samples lead to the emergence of an discrete peak at $\cong 2468 \text{cm}^{-1}(D+D'')$ band, Table S2), which is typically characteristic of graphene [44]. The displacements observed in the band positions (Table S2) are indicative of the doping of the GNR structure with different elements [29]. Also, the change in the I_D/I_G ratio helps confirm the doping of GNR structures with different elements and the variation in defects [31,34,45,52]. In comparison with undoped GNR (I_D/I_G ratio = 1.72), when N is introduced as a dopant in GNR, the number of defects decreases (resulting in a lower ID/IG ratio). Conversely, S doping increases the number of defects yielding a higher ID/IG ratio, while P doping changes moderately as shown in decreases the defects' number (resulting in a closer ID/IG ratio). Co-doping GNR with NS and NSP discreetly increases the defects' number (I_D/I_G ratio = 1.79 and 1.76, respectively) and the NP co-doping of GNR is identical in defects' number (ID/IG ratio = 1.72). Finally, SP co-doping of GNR reduces the defects' number (ID/IG ratio = 1.58, as shown in Table S2). The tendency' reason in the Ip/Ic ratio for the different materials can be explained by the significant reduction in the amount of O-functional groups in GNR doped with nitrogen, leading to a decrease in edges/defects after nitrogen doping (detailed in the next section). On the other hand, in the case of doping with S and/or P, these larger-sized elements (higher

3.2. XPS, EA and TGA Study

The survey XPS spectra (Figure S1) show the presence of C 1s and O 1s peaks at 285 and 533 e V, respectively, and a very small O KLL peak at 974 eV for all the samples; also, the spectra show the presence of a N 1s peak at 400 eV (Table S3) for the N-containing modified GNR.

than carbon) contribute to an increase in edges/defects after doping.

The average values of the mass percentage composition obtained for the modified GNRs are as follows: 87.4 and 10.1% for C 1s and O 1s, respectively, and 4.3% for N 1s (Table S3). These values are quite close to the values corresponding to C and O obtained from the elemental analyses (EA) – where we recorded average values of mass percentage composition of 83.6 and 8.1%, respectively, and 2.3% for N (Table S4). Individually, some of these compositions are even closer to each other (compare Tables S3-4).

The results obtained from the EA (Table S4) show that the amount of N is increased considerably for the GNR doped with N (3.0–6.2 wt.%) in comparison with the undoped GNR (1 wt.%); the amount of O is significantly diminished in the GNR doped with nitrogen (lower amount of O:4-5 wt.%) compared to the undoped GNR (9.7 wt.%); the amount of H is 1.5% on average for the doped GNR or undoped GNR; and finally, an amount of 4 wt.% is recorded on average for other elements in the doped GNR or undoped GNR. Taking into account the due proportion of the materials, the different catalysts investigated exhibited similar behavior in terms of mass percentage composition of C, O, and N - as shown in Table S3.

The results obtained from the thermogravimetric analyses showed that the undoped GNR exhibited mass loss similar to that previously reported in the literature [53–55]. In addition, when considering the temperature region — between 552 and 666 °C — within which effective burning of the undoped GNR occurred, the doped GNR exhibited variations in the mass loss curve region, ranging from 53 °C (lower) to 23 °C (higher) compared to the mass loss region of the undoped GNR; furthermore, we noted some residual mass % after 700 °C (Figure S2), which is in agreement with the residual wt.% detected through EA (Table S4).

Figure 3 shows the C, O, and N 1s core-level XPS spectra obtained for the doped GNR samples after peak deconvolution.




Figure 3. HR-XPS curves for the undoped and doped GNR samples.

The C 1s spectra show a very accentuated peak and a small shoulder (Figure 3, first column) which were deconvoluted into five to seven peaks attributed to the chemical states C=C & C-C, C-OH &C-O-C, C-S, C-P, C-N, C=O & COOH, and $\pi-\pi$ positioned on average at 285, 286, 286.8, 287.1, 287.8, 288.7, and 290.1 eV, respectively (Table S5). Overall, these results are in agreement with the results reported in the literature [11–13,55–58]. The C 1s spectra deconvoluted into the peaks related

to the chemical states of C–S and/or C–P and/or C–N for the different catalysts further confirm the modifications produced by these atoms in the GNR structure. Also, on average, the main contributions in terms of % content come from C=C & C-C and C–OH & C–O–C chemical states with 76.7%, followed by (on average) C–S (9.6%), C–P (8.7%), and C–N (6%) (Table S5). The last information confirms the doping of GNR with S and/or P and/or N.

The O 1s spectra, in general, exhibited a broad peak (Figure 3, second column) which was deconvoluted into two or three peaks attributed to the chemical states of C=O, C-O and H_2O , and positioned on average at 532.3, 534, and 536.6 eV, respectively [11–13,55–58] (Table S5). The main contribution in terms of % content came from the chemical states of C=O and C-O, with an average of 96.5% (Table S5).

The N 1s spectra also displayed a broad peak (Figure 3, third column), which was deconvoluted into the pyridinic-N, pyrrolic-N, graphitic-N, and oxidized-N peaks, positioned on average at 398.8, 399,8, 401, and 403 eV, respectively [11–13,55–58] (Table S5); here, the main contributions in terms of % content came from pyrrolic-N and graphitic-N chemical states with an average of 35.2 and 39%, respectively, followed by pyridinic-N with an average of 20.8% (Table S5).

Figure S3 shows the HR-XPS spectra for P 2p, S 2p, Cl 2p, Mn 2p, and Fe 2p, which are constituted mostly of noise; this shows that the P and S elements exhibited low signal and low amounts of contaminants (Cl, Mn, and Fe) remained after the synthesis of the undoped GNR and doped GNR.

3.3. XRD, TEM, and EDX Study

The X-ray diffraction (XRD) technique was used to investigate the effect of the doping process on the crystalline structure of GNR. Figure S4 shows the diffraction patterns obtained for the undoped and doped GNR.

The results obtained from the XRD analyses show that the doped GNR exhibits a prominent peak at 2θ = 25.8° (0.35 nm), which is typically characteristic of crystalline peak for the theoretical C graphite with (110) plane (PDF89-8489) and a small peak displacement at 2θ , depending on the doping element in comparison with the undoped GNR (Figure S4). Also, there is a small peak at 2θ = 42.7–43°(0.21 nm) related to the plane (201) (PDF 89-8489) and a shoulder at 2θ = 18.8°, which is typically associated with the doped GNR. These results also help to confirm the doping of GNR.

From the TEM images (Figures 4 and S5), one can clearly see the GNR (MWCNT opened structures) with a plenty of edges in the structure; however, one is unable to clearly see the differences between the doped and undoped GNR samples. The selected area electron diffraction (SAED) patterns of the samples discreetly display the undoped and doped GNR spots with low crystallinity. Furthermore, the observed ring pattern for all the samples is related to the lack of crystallographic orientation between the GNR [59]. For the different doped GNR samples, the EDX mapping images (Figure 5) show a regular distribution of the doping elements (N, S, and P) and a high dispersion of oxygen atoms.




Figure 4. TEM and electron diffraction pattern images for the undoped and doped GNR samples.




Figure 5. Scanning TEM and EDX mapping images obtained for the undoped and doped GNR samples.

3.4. Electrochemical Study - ECSA and CV Profile

The undoped and doped GNR samples were characterized electrochemically by cyclic voltammetry (CV) using N2-saturated 0.5 M H2SO4, 0.1 M K2SO4 and 0.1 M KOH electrolyte solutions; the results obtained are shown in Figure 6a-f. Based on the CV obtained from the N₂-saturated 0.5 M H₂SO₄, the undoped GNR (Figure 6a) exhibited capacitive behavior, characterized by double layer charging and discharging currents, and redox peaks around 0.6 V, which are typically attributed to the presence of quinone groups on the GNR surface [11,54]. Quinones are known to have high selectivity for the production of H2O2 when present on the edges and basal planes of carbon nanostructures [60]. During the ORR, these quinone groups can also act as electron acceptors, facilitating efficient electron transfer from the electrode to the reaction intermediates. In general, heteroatom-doped or co-doped GNR samples exhibited two distinguishable patterns of electrochemical behavior (CV shapes) and differences in capacitive current values. Although doping, in general, made the redox pair at ca. 0.6 V less pronounced (GNRP and GNRSP samples, Figure 6a), a closer look at the results showed that the GNRS samples exhibited a more pronounced redox couple related to the quinone/hydroquinone process (q/h); this implies the presence of higher contents of oxygen-functional groups in comparison to other undoped and doped GNR samples - this observation is in good agreement with the XPS results (c.f. Table S3). The noticeable appearance of the q/h redox peak leads to a more symmetrical CV profile with the shape of a pseudo capacitor (c.f. Figure 6) [61–63]. On the other hand, an intensification of the smoothing of the q/h peak leads to the formation of a profile that resembles an irregular quadrilateral object (c.f. Figure 6b, GNRNS and GNRNSP samples), which is found to be typically associated with a purer electrical double-layer (DL) capacitor; this capacitor is able to store charge electrostatically through the DL without the contribution of the faradaic q/h process [61–63].




Figure 6. CV obtained for the GC electrodes modified with 150 μ g cm⁻² of undoped or doped GNR applied in N₂-saturated 0.5 M H₂SO₄, 0.1 M K₂SO₄, and 0.1 M KOH. Potential scan rate: 50 mV s⁻¹ (scans were initiated at 1.2 V).

Based on the CV obtained in neutral medium (Figure 6c,d), we observed, in general, that all the undoped or heteroatom-doped or co-doped GNR samples exhibited similar electrochemical behavior with slight changes in the capacitive current values. Regarding the shape of the CV, in neutral media, the GNRS and GNRSP samples (Figure 6c) exhibited relatively less pronounced q/h redox peaks (purer electrical DL capacitor behavior); this implies that the depletion of H⁺ exerts a significant influence over the capacitive ability.

In alkaline medium (Figure 6e,f), in general, the CVs exhibited similar shape for the undoped or heteroatom doped or co-doped GNR and slightly high capacitive currents in comparison with the CVs obtained in neutral medium; this points to the effect of the doping process on the capacitive ability of graphene nanoribbons. Regarding the q/h redox peaks, the GNRS and GNRSP (Figure 6e)

exhibited the most accentuated q/h peaks compared to the other samples (Figure 6f); this shows that the insertion of S in isolation or in combination with P exerts a strong influence over the q/h redox process of the GNR sample, and this leads to a more pseudo capacitive behavior in alkaline media. In general, all the other heteroatom-doped or co-doped GNR samples exhibited similar electrochemical behavior with a purer electrical DL capacitor CV profiles and high capacitive current values - of around 350 μ A.

Table 2 shows the DL capacitance (Cdl) and the electrochemical surface area (ECSA) values obtained for the undoped and doped GNR samples in different media. Overall, the results obtained show that the Cdl and ECSA are highest in acidic medium, lower in neutral medium, and lowest in alkaline medium. The GNRN catalyst recorded the highest ECSA in acidic media - ca. 159.4 cm². This increase in ECSA can be attributed to two key factors. Firstly, the redox processes associated with the presence of more basic functional groups, such as quinones, pyridinic-N, and pyrrolic-N groups (which require protons for the overall redox processes), significantly contribute to the enhanced capacitance and ECSA. Secondly, the introduction of N atoms in the GNR leads to a reduction of the stacking effect on graphene nanoribbons, resulting in a modified electronic structure. This reduction enhances accessibility to the carbon structure, leading to a more pseudo-capacitive behavior and ultimately a higher ECSA value [64]. On the other hand, the GNRSP catalyst recorded the lowest ECSA in neutral and alkaline media, with values of approximately 37.4 and 8 cm², respectively. These results suggest that the presence of 2 or 3 dopants tends to decrease the ECSA. The differences in CdI and ECSA observed from the use of different electrolyte solutions are related to the differences in the physical-chemical properties of the electrolytes – such as pH, size and charge of ions in the electrolyte solution (i.e., hydroxyl has smaller charge-to-mass ratio than sulfate ion), and resistance (c.f. Table S6 and Figure S6), as previously reported in the literature [65]. Particularly GNRP, which exhibited an opposite trend with higher capacitance in alkaline medium, we attribute this difference to the lower electronegativity of phosphorus atoms compared to carbon atoms and the ability of phosphorus to modulate the charge densities of carbon, allowing negatively charged species to approach the electrode surface and participate in the redox processes. Our results suggest that P-doped samples do not necessarily depend on the presence of protons to exhibit high values of Cdl and ECSA. However, it is important to note that the behavior of different samples can be influenced by various factors, and further investigation is needed to fully understand and explain the observed variations.

Table 2. Comparative analysis of the physical-chemical properties and ORR parameters of the undoped and doped GNR catalysts in different media. The table provides the following relevant data for the catalysts investigated: C_{dl} values obtained from the data in Figures S7–S9, ECSA values obtained from the data in Figure S10, ORR onset potential values (E_{onset}), potential at half limiting current density values (E_{1/2}), number of electrons obtained from the RRDE plot (n_{av}), and peroxide percentage (X HO₂-(%)) obtained from the data in Figures 7 and S11–12.

Catalyst	Dopant Element (at%)*	Cdl (µF)	ECSA** (cm²)	Electrolyte	Eonset (VRHE) ***	E _{1/2} (V _{RHE})	X HO ₂ - (%)****	nav****
GNR	-	2248.4	132.3	0.5 M H ₂ SO ₄	0.26	0.13	76.7	2.5
GNR	-	1265.8	74.5	0.1 M K ₂ SO ₄	0.89	0.73	5.2	3.9
GNR	-	1287.6	58.5	0.1 M KOH	0.83	0.66	55.7	2.9
GNRN	N (2.5 at%)	2709.5	159.4	0.5 M H ₂ SO ₄	0.41	0.24	57.7	2.8
GNRN	N (2.5 at%)	1228.4	72.3	0.1 M K ₂ SO ₄	0.90	0.72	5.3	3.9
GNRN	N (2.5 at%)	1454.4	66.1	0.1 M KOH	0.86	0.74	29.9	3.4
GNRS	S (nq)	2262.4	133.1	0.5 M H ₂ SO ₄	0.33	0.20	52.3	3.0
GNRS	S (nq)	1394.9	82.1	0.1 M K ₂ SO ₄	0.76	0.62	23.8	3.5
GNRS	S (nq)	1921.8	87.4	0.1 M KOH	0.83	0.66	41.4	3.2

GNRP	P (nq)	1409.4	82.9	0.5 M H ₂ SO ₄	0.45	0.28	35.3	3.3
GNRP	P (nq)	754.5	44.4	0.1 M K ₂ SO ₄	0.88	0.68	13.7	3.7
GNRP	P (nq)	2316.8	105.3	0.1 M KOH	0.79	0.58	26.7	3.5
	N (3.6							
GNRNS	at%)	1190.0	70.0	0.5 M H ₂ SO ₄	0.42	0.24	41.5	3.2
	S (nq)							
	N (3.6							
GNRNS	at%)	1112.1	65.4	0.1 M K ₂ SO ₄	0.88	0.66	12.5	3.7
	S (nq)							
	N (3.6							
GNRNS	at%)	892.3	40.6	0.1 M KOH	0.85	0.71	30.5	3.4
GI VIII V	S (nq)			01-11-1-1		V		
	N (4.3							
GNRNP	at%)	2389.6	140.6	0.5 M H ₂ SO ₄	0.33	0.18	91.5	2.2
0111111	P (nq)		110.0	0.0 1.1 1 120 0 1	0.00	0.10	71.0	
	N (4.3							
GNRNP	at%)	667.5	39.3	0.1 M K ₂ SO ₄	0.79	0.60	11.9	3.8
GIVICIVI	P (nq)	007.0	07.0	0.1 111 12004	0.7 5	0.00	11.7	0.0
	N (4.3							
GNRNP	at%)	906.9	41.2	0.1 M KOH	0.69	0.53	30.1	3.4
GIVICIVI	P (nq)	700.7	41,2	0.1 W ROTT	0.07	0.55	50.1	0.1
	P (nq)							
GNRSP	S (nq)	722.5	42.5	0.5 M H ₂ SO ₄	0.30	0.17	94.5	2.1
	P (nq)							
GNRSP	S (nq)	635.9	37.4	0.1 M K ₂ SO ₄	0.80	0.62	53.1	2.9
	P (nq)							
GNRSP	S (nq)	175.1	8.0	0.1 M KOH	0.83	0.65	48.7	3.0
	N (4.6							
GNRNSP	at%)							
	P (nq)	881.4	51.8	$0.5~\mathrm{M}~\mathrm{H}_2\mathrm{SO}_4$	0.41	0.25	48.6	3.0
	S (nq)							
	N (4.6							
GNRNSP	at%)							
	P (nq)	735.5	43.3	0.1 M K ₂ SO ₄	0.87	0.71	18.9	3.6
	S (nq)							
	N (4.6							
	at%)							
GNRNSP	P (nq)	624.7	28.4	0.1 M KOH	0.85	0.72	32.4	3.3
	S (nq)							
	<i>5</i> (114)							

*Value estimated from XPS data (Table S3). nq = detected by XPS, EA and/or EDX but not quantified. **The ECSA values were estimated by dividing CdI by the specific capacitance. The specific capacitance values were estimated based on the capacitance of an atomically smooth planar carbon-based material surface per unit area under acidic (17 μ F cm⁻²), neutral (We make the same assumption as the acidic medium: 17 μ F cm⁻²), and alkaline (22 μ F cm⁻²) conditions, as described in ref. [66]. The ΔI values were divided by 2 (($\Delta I = I_a - I_c$)/2), and the current values obtained were measured at the OCP as a function of v (Figure S10). The slopes of these plots give the CdI values, which are used to determine the ECSA. *** The Eonset values were determined based on the point at which the disk current density reached -0.05 mA cm⁻². ****. The X HO₂-(%) and n_{av} values were calculated (see equations S1-2) within the potential range starting from the lower potential (the potential at which the LSV curve begins) and extending to the onset (Eonset).




Figure 7. Results obtained from the LSV analysis conducted in a RRDE system for GC modified with 150 μ g cm⁻² of undoped or doped GNR catalysts under the following conditions: scanning at the potential of 10 mV s⁻¹; RRDE rotation at 1600 rpm; electrolyte solutions applied: O2⁻ saturated 0.5 M H₂SO₄, 0.1 M K₂SO₄, and 0.1 M KOH (scans were initiated at 0.05 or –0.3 V).

3.5. Analysis of ORR Activity and Selectivity

3.5.1. 0.5 M H₂SO₄ Solution

Initially, we evaluated the ORR activity and selectivity of the undoped and doped GNR samples in O₂–saturated 0.5 M H₂SO₄ using linear sweep voltammetry (LSV) in a RRDE system. The results, presented in Figure 7a,b, show that the undoped GNR catalyst had an ORR onset potential of 0.26 V; this shows that the catalyst exhibited relatively less efficient activity compared to the metal-based catalysts like Pt [67]. After the doping process, the GNR doped with P exhibited the highest improvement in ORR activity among the samples, with an onset potential (E_{onset}) of 0.45 V, followed by GNRNS and GNRN (also GNRNSP) with E_{onset} of 0.42 V and 0.41 V, respectively - values obtained for all the samples can be found in Table 2. In terms of selectivity (Figures S11–12), the GNRSP and GNRNP catalysts were found to be more favorable to ORR via the 2e- pathway, exhibiting over 90%

selectivity (n \approx 2.2) toward H₂O₂ production (X_{H2O2}), while pristine GNR recorded 77% selectivity (n \approx 2.5). On the other hand, the GNRP, GNRNS, and GNRNSP catalysts recorded X_{H2O2} of ca. 42% (n \approx 3.2) on average; this shows that the doping of GNR with P concomitantly or not with N and S boosted the catalytic activity and favored the occurrence of ORR through the 4e- pathway in acidic media (c.f. Table 2). Furthermore, the accelerated stress test conducted in the potential range of 0.6 to 1.0 V at 1 V s⁻¹ (Figure S13) showed that the catalytic performance of the GNRP remained stable even after 10 000 potential cycles; this outcome is confirmed by the undetectable changes in the TEM and electron diffraction pattern images of the catalyst (Figure 4), as well as its scanning TEM (STEM) and EDX mapping images (Figure 5) - named GNRPes (GNRP after electrochemical stability).

3.5.2. 0.1 M K₂SO₄ Solution

In neutral medium (Figure 7c,d), the doping process only led to improvements in ORR catalytic activity when GNR was doped with nitrogen. The undoped GNR catalyst exhibited an ORR onset potential of 0.89~V, while the GNRN catalyst exhibited a modest improvement with E_{onset} of 0.90~V. The other heteroatom doped and co-doped catalysts exhibited E_{onset} lower than 0.89~V - see the values in Table 2.

When GNR was doped with S, for instance, the E_{onset} decreased significantly from 0.89 to 0.76 V; this outcome shows that the insertion of S atoms in GNR provoked a negative impact on the catalytic activity and the decrease in O content reflected the observed catalytic deactivation. In terms of selectivity (Figures S11–12), GNR doped with phosphorus and sulfur favored the occurrence ORR via the 2e⁻ pathway; for illustration purposes, GNRSP exhibited 53% selectivity toward H_2O_2 production (n \approx 2.9), while pristine GNR exhibited 5.2% selectivity (n \approx 3.9). On the other hand, GNR doped with nitrogen (GNRN, GNRNP, GNRNS, and GNRNSP samples with $X_{HO2} \approx 12\%$ and n \approx 3.8, on average) favored the occurrence of ORR via the $4e^-$ pathway.

3.5.3. 0.1 M KOH Solution

In general, the LSV curves in alkaline medium (Figure 7e,f) show characteristic behavior of a $2e^-$ (from around 0.8 to 0.4 V) + $2e^-$ (from around 0.2 to -0.3 V) mechanism, in accordance with the behavior of X_{HO2-} (Figure S11) and n_{av} (Figure S12).

The doping of GNR with nitrogen caused a significant effect on the catalytic performance in ORR. The GNRN catalyst exhibited an ORR onset potential of 0.86 V, while the undoped GNR catalyst recorded an onset potential of 0.83 V. Both the GNRNSP and GNRNS catalysts recorded Eonset of 0.85 V; this result points to an improvement in catalytic performance following the insertion of N, S and P groups concomitantly into the GNR matrix. Compared to GNR, no improvements were observed in the GNRS and GNRSP samples; however, when these catalysts were doped with P (GNRP and GNRNP catalysts), they recorded Eonset values lower than 0.83 V; this shows that Pdoping, either alone or in combination with other elements, leads to the loss of catalytic activity for graphene matrix in alkaline media. The MWCNT oxidized and doped with N and S (MWCNToxNS) produced by Wierzbicki et al. [68] results in better E_{1/2} value (better activity and selectivity to H₂O) in comparison with our catalysts. In terms of selectivity, the undoped GNR catalyst exhibited the highest selectivity toward H₂O₂ production, reaching ca. 56% (n ≈ 2.9) in the potential range of -0.3 to 0.7 V. In line with previous studies reported in the literature [11,57], GNR presented two distinct potential regions with high selectivity. The first region, between 0.70 to 0.35 V, favored H₂O₂ formation (X_{HO2-} = 90%, n \approx 2.2), while the second region, between 0.30 to -0.30 V, favored water formation (XHO2-= 30%, n ≈ 3.2). It should be noted however that heteroatom doping or co-doping of GNR is found to decrease H₂O₂ selectivity, particularly when GNR is doped with P and N - this results in X_{HO2-} lower than 30% (n \geq 3.4).

3.6. Comparative Analyses and Assessment of Trends

The results obtained from the characterization of the samples investigated in this study showed that, in general, the heteroatom doping or co-doping of GNR did not lead to significant structural

19

modifications (- see TEM results). However, the analysis of the surface chemistry of the materials helped identify the presence of a doping process which led to the insertion of the heteroatom concomitantly with oxygen depletion, as well as variation in defects (no present clear influence on the ORR activity and selectivity toward H₂O₂ as pointed out below). In addition, the results also showed that the electrolyte solution [69] and heteroatom doping or co-doping [70-73] exerted considerable influence on ORR activity and selectivity in the doped GNR samples (including in comparison with the undoped GNR). Among the dopant elements investigated, N (mainly in the form of Pyrrolic-N and Graphitic-N) was found to be the most easily inserted (and detected) in the carbon matrix. The results obtained from the electrochemical analysis showed that heteroatom insertion and oxygen depletion after doping also affected the visual intensity of the q/h redox peak and the voltammetric profile, and this exerted influence over the Cal and ECSA values. Heteroatomdoped or co-doped GNR samples exhibited two distinct patterns of electrochemical behavior and differences in capacitive currents. The doped samples that exhibited a more noticeable q/h redox couple, with higher contents of O-groups, had a more symmetrical CV profile, which resembled that of a pseudo capacitor; overall, these samples exhibited lower ORR activity with higher selectivity toward H₂O₂ formation in both acidic, neutral and alkaline media. On the other hand, samples with CV profiles that indicated the absence or smoothing of the q/h peak exhibited a profile that resembled a pure electrical double-layer capacitor; overall, these samples exhibited enhanced ORR activity and higher selectivity toward water (or OH) formation – this is in line with the catalyst responses shown in other works previously reported in the literature [24,26,29-31,33]. Essentially, these results also suggest that the noticeable appearance of the redox couple peaks related to the q/h process in an electrochemical profile is a strong indicator of the selective formation of H₂O₂, and this observation can be applied to ORR in different media. In general, N-doping yielded the most efficient result in terms of ORR-4e- catalytic performance for solutions with high pH. For illustration purposes, N and NSP-doping (GNRN and GNRNSP samples) improved ORR catalytic activity in neutral medium. These findings regarding the catalysts doped and co-doped with N can be explained in accordance with the Xia et al. [19] model. The protonation of N groups introduced during the doping process on the catalyst surface may hinder charge delocalization, thereby compromising the electrocatalytic activity in acidic media and promoting the formation of H2O2. On the other hand, the doping of graphene nanoribbons with S and P (GNRS and GNRP, respectively) led to improvements in ORR activity only in acidic media, with the occurrence of ORR seen to be favored under the 4e- pathway. Interestingly, in neutral and alkaline media, the doping of GNR with S and P led to a decline in ORR activity; this outcome can be attributed to the ability of S and P to generate sulfonic or phosphonic acid groups that can act as proton donors, facilitating the transfer of electrons [74,75]. The results obtained from the experiments conducted in this study also showed that the co-addition of sulfur and phosphorus to graphene nanoribbons (GNRSP) led to a higher formation of H₂O₂ in all the three media conditions evaluated in the study; this is likely because of the adsorption of oxygen molecules in the Pauling-type form in the carbon atoms near the sulfur or phosphorus atoms on the catalyst surface, which made it easier for the HOOH or OOH⁻ to be released after the two-electron transfer in the ORR process [76,77]. Furthermore, our findings also showed that the addition of two or three elements to graphene does not lead to a significant enhancement of its catalytic activity.

To gain insights into the ORR mechanism in different samples and media, Tafel plots were constructed for selected catalysts, namely GNRSP and GNRNS, as depicted in Figure S14. Generally, the Tafel slopes of both electrocatalysts are relatively similar, indicating that the introduction of heteroatoms through doping does not significantly alter the reaction pathway. However, notable differences can be observed in their catalytic activities when exposed to alkaline and acidic media. In alkaline conditions, which exhibit an average Tafel slope of 60 mV dec-1, a faster and higher catalytic activity is observed. On the other hand, at lower pH values, the slope values are relatively close and higher, averaging around 100 mV dec-1. This suggests the involvement of additional reaction steps. The difficulty of the ORR in acidic media may be attributed to the protonation of functional groups within the carbon matrix. This protonation reduces the interaction with molecular oxygen, impairing the ORR and requiring high overpotentials for O2 adsorption and subsequent reduction to occur. In

contrast, in alkaline media, the deprotonated functional groups exhibit a negative nature, facilitating the removal of OH⁻ ions and promoting the adsorption of O₂ on the carbon matrix surface. These observations highlight the influence of pH on the ORR process, with acidic media presenting challenges due to functional group protonation, while alkaline media provide a favorable environment for O₂ adsorption and subsequent reduction.

4. Conclusions

In summary, in the present study, we successfully produced carbon catalysts doped and codoped with N, S, and P using the same graphene (GNR) matrix. A wide-ranging analysis was conducted in order to evaluate the impact of doping on ORR catalytic activity and selectivity in acidic, neutral, and alkaline media. The results obtained from the characterization of the materials investigated showed that the doping process resulted in the insertion of heteroatoms and oxygen depletion, with nitrogen (in the form of pyrrolic-N and graphitic-N) being the most easily inserted among the dopants. Electrochemical characterization analysis showed that the insertion of heteroatoms and oxygen depletion affect the intensity of the q/h redox peak and voltammetric profile, leading to differences in capacitive currents and ORR selectivity. The results obtained from the electrochemical characterization analysis showed that the noticeable intensity of the redox couple peaks related to the quinone/hydroquinone process in a CV profile is a strong indicator of ORR selectivity toward H₂O₂ formation, and this observation can be applied for ORR in different media. In terms of the catalytic performance of the elements used for doping GNR, nitrogen was found to be the most efficient element (its application led to significant improvements in catalytic activity) for solutions with high pH, while sulfur and phosphorus improved ORR activity only in acidic medium. The co-doping of GNR with S and P resulted in ORR selectivity toward the formation of hydrogen peroxide in all the three media investigated (acidic, neutral, and alkaline). The results of the study also showed that co-doping with two or three elements did not lead to significant catalytic improvements. The findings of the present study provide useful insights into carbon functionalization and can serve as a pivotal roadmap for the design of more formidable and versatile catalytic materials based on functionalized carbon.

Supplementary Materials: The following supporting information can be downloaded at the website of this paper posted on Preprints.org. The supporting information contains experimental details, figures, equations, and tables related to supplementary results.

Acknowledgements: The authors would like to thank the following Brazilian research funding agencies for their financial assistance: Brazilian National Council for Scientific and Technological Development - CNPq (grants #465571/2014-0, #302874/2017-8, #427452/2018-0, #303351/2018-7, #405742/2018-5, #380886/2020-0, #303943/2021-1, #302561/2022-6, # 151161/2023-2), Fundect-MS (grants #71/020.168/2021, #71/027.195/2022 and #71/039.199/2022), and CAPES-PRINT (grant #88881.311799/2018-01). São Paulo Research Foundation (FAPESP – grants #2014/50945-4, #2017/10118-0, #2019/04421-7, and #2023/01425-7). E.S.F. Cardoso would also like to extend his gratitude to PNPD-CAPES and Coordenação de Aperfeiçoamento de Pessoal de Nível Superior (CAPES – Finance Code 001) for the financial assistance provided during this research. The authors would also like to thank the Laboratory of Structural Characterization (LCE/DEMa/UFSCar) for providing general facilities for the experiments.

Conflict of Interest: The authors declare no competing financial interest.

References

- Xu, M.; Liang, T.; Shi, M.; Chen, H. Graphene-Like Two-Dimensional Materials. Chem. Rev. 2013, 113, 3766–3798, doi:10.1021/cr300263a.
- 2. Chen, Z.; Narita, A.; Müllen, K. Graphene Nanoribbons: On-Surface Synthesis and Integration into Electronic Devices. *Adv. Mater.* **2020**, *32*, 2001893, doi:https://doi.org/10.1002/adma.202001893.
- 3. Huang, C.; Li, C.; Shi, G. Graphene Based Catalysts. *Energy Environ. Sci.* **2012**, *5*, 8848, doi:10.1039/c2ee22238h.
- 4. Gu, Y.; Qiu, Z.; Müllen, K. Nanographenes and Graphene Nanoribbons as Multitalents of Present and Future Materials Science. *J. Am. Chem. Soc.* **2022**, 144, 11499–11524, doi:10.1021/jacs.2c02491.

- Kosynkin, D. V; Higginbotham, A.L.; Sinitskii, A.; Lomeda, J.R.; Dimiev, A.; Price, B.K.; Tour, J.M. Longitudinal Unzipping of Carbon Nanotubes to Form Graphene Nanoribbons. *Nature* 2009, 458, 872–876, doi:10.1038/nature07872.
- 6. Mohanty, N.; Moore, D.; Xu, Z.; Sreeprasad, T.S.; Nagaraja, A.; Rodriguez, A.A.; Berry, V. Nanotomy-Based Production of Transferable and Dispersible Graphene Nanostructures of Controlled Shape and Size. *Nat. Commun.* **2012**, *3*, 844, doi:10.1038/ncomms1834.
- 7. De Lima, F.; Maia, G. Oxidized/Reduced Graphene Nanoribbons Facilitate Charge Transfer to the Fe(CN)63-/Fe(CN)64- Redox Couple and towards Oxygen Reduction. *Nanoscale* **2015**, 7, 6193–6207, doi:10.1039/c5nr01123j.
- 8. Li, J.; Zhao, Z.; Ma, Y.; Qu, Y. Graphene and Their Hybrid Electrocatalysts for Water Splitting. *ChemCatChem* **2017**, *9*, 1554–1568, doi:https://doi.org/10.1002/cctc.201700175.
- 9. Rogers, C.; Perkins, W.S.; Veber, G.; Williams, T.E.; Cloke, R.R.; Fischer, F.R. Synergistic Enhancement of Electrocatalytic CO2 Reduction with Gold Nanoparticles Embedded in Functional Graphene Nanoribbon Composite Electrodes. *J. Am. Chem. Soc.* **2017**, 139, 4052–4061, doi:10.1021/jacs.6b12217.
- de Souza, M.K.R.; Cardoso, E. dos S.F.; Fortunato, G. V.; Lanza, M.R.V.; Nazário, C.E.; Zanoni, M.V.B.; Maia, G.; Cardoso, J.C. Combination of Cu-Pt-Pd Nanoparticles Supported on Graphene Nanoribbons Decorating the Surface of TiO2 Nanotube Applied for CO2 Photoelectrochemical Reduction. *J. Environ. Chem. Eng.* 2021, 9, 105803, doi:10.1016/j.jece.2021.105803.
- 11. Cardoso, E.S.F.; Fortunato, G. V.; Maia, G. Use of Rotating Ring-Disk Electrodes to Investigate Graphene Nanoribbon Loadings for the Oxygen Reduction Reaction in Alkaline Medium. *ChemElectroChem* **2018**, *5*, 1691–1701, doi:10.1002/celc.201800331.
- 12. Cardoso, E.S.F.; Fortunato, G. V.; Maia, G. Modification of C, O, and N Groups for Oxygen Reduction Reaction on an Electrochemically Stabilized Graphene Nanoribbon Surface. *J. Phys. Chem. C* **2019**, 123, 16308–16316, doi:10.1021/acs.jpcc.9b04422.
- 13. Bezerra, L.S.; Maia, G. Developing Efficient Catalysts for the OER and ORR Using a Combination of Co, Ni, and Pt Oxides along with Graphene Nanoribbons and NiCo2O4. *J. Mater. Chem. A* **2020**, *8*, 17691–17705, doi:10.1039/d0ta05908k.
- Cruz-Silva, R.; Morelos-Gómez, A.; Vega-Díaz, S.; Tristán-López, F.; Elias, A.L.; Perea-López, N.; Muramatsu, H.; Hayashi, T.; Fujisawa, K.; Kim, Y.A.; et al. Formation of Nitrogen-Doped Graphene Nanoribbons via Chemical Unzipping. ACS Nano 2013, 7, 2192–2204, doi:10.1021/nn305179b.
- 15. Duan, J.; Chen, S.; Jaroniec, M.; Qiao, S.Z. Heteroatom-Doped Graphene-Based Materials for Energy-Relevant Electrocatalytic Processes. *ACS Catal.* **2015**, *5*, 5207–5234, doi:10.1021/acscatal.5b00991.
- 16. Ma, R.; Lin, G.; Zhou, Y.; Liu, Q.; Zhang, T.; Shan, G.; Yang, M.; Wang, J. A Review of Oxygen Reduction Mechanisms for Metal-Free Carbon-Based Electrocatalysts. *npj Comput. Mater.* **2019**, *5*, 78, doi:10.1038/s41524-019-0210-3.
- 17. Yang, Z.; Yao, Z.; Li, G.; Fang, G.; Nie, H.; Liu, Z.; Zhou, X.; Chen, X.; Huang, S. Sulfur-Doped Graphene as an Efficient Metal-Free Cathode Catalyst for Oxygen Reduction. *ACS Nano* **2012**, *6*, 205–211, doi:10.1021/nn203393d.
- 18. Noffke, B.W.; Li, Q.; Raghavachari, K.; Li, L. A Model for the PH-Dependent Selectivity of the Oxygen Reduction Reaction Electrocatalyzed by N-Doped Graphitic Carbon. *J. Am. Chem. Soc.* **2016**, *138*, 13923–13929, doi:10.1021/jacs.6b06778.
- 19. Wan, K.; Yu, Z.P.; Li, X.H.; Liu, M.Y.; Yang, G.; Piao, J.H.; Liang, Z.X. PH Effect on Electrochemistry of Nitrogen-Doped Carbon Catalyst for Oxygen Reduction Reaction. *ACS Catal.* **2015**, *5*, 4325–4332, doi:10.1021/acscatal.5b01089.
- 20. Lv, Q.; Si, W.; He, J.; Sun, L.; Zhang, C.; Wang, N.; Yang, Z.; Li, X.; Wang, X.; Deng, W.; et al. Selectively Nitrogen-Doped Carbon Materials as Superior Metal-Free Catalysts for Oxygen Reduction. *Nat. Commun.* **2018**, *9*, 3376, doi:10.1038/s41467-018-05878-y.
- 21. Iglesias, D.; Giuliani, A.; Melchionna, M.; Marchesan, S.; Criado, A.; Nasi, L.; Bevilacqua, M.; Tavagnacco, C.; Vizza, F.; Prato, M.; et al. N-Doped Graphitized Carbon Nanohorns as a Forefront Electrocatalyst in Highly Selective O2 Reduction to H2O2. *Chem* **2018**, *4*, 106–123, doi:10.1016/j.chempr.2017.10.013.
- 22. Wang, S.; Liu, Y.; Liu, X.; Chen, Y.; Zhao, Y.; Gao, S. Fabricating N, S Co-Doped Hierarchical Macro-Meso-Micro Carbon Materials as PH-Universal ORR Electrocatalysts**. *ChemistrySelect* **2022**, 7, e202200044, doi:10.1002/slct.202200044.
- 23. Kolle-Görgen, E.; Fortunato, G.; Ledendecker, M. Catalyst Stability in Aqueous Electrochemistry. *Chem. Mater.* **2022**, *34*, 10223–10236, doi:10.1021/acs.chemmater.2c02443.
- 24. Xiang, T.; Wu, Z.; Sun, Z.; Cheng, C.; Wang, W.; Liu, Z.; Yang, J.; Li, B. The Synergistic Effect of Carbon Edges and Dopants towards Efficient Oxygen Reduction Reaction. *J. Colloid Interface Sci.* **2022**, *610*, 486–494, doi:10.1016/j.jcis.2021.11.069.
- 25. Dong, F.; Cai, Y.; Liu, C.; Liu, J.; Qiao, J. Heteroatom (B, N and P) Doped Porous Graphene Foams for Efficient Oxygen Reduction Reaction Electrocatalysis. *Int. J. Hydrogen Energy* **2018**, 43, 12661–12670, doi:10.1016/j.ijhydene.2018.04.118.

- 26. Han, C.; Chen, Z. The Mechanism Study of Oxygen Reduction Reaction (ORR) on Non-Equivalent P, N Co-Doped Graphene. *Appl. Surf. Sci.* **2020**, *511*, 145382, doi:10.1016/j.apsusc.2020.145382.
- 27. Zhao, G.; Shi, L.; Xu, J.; Yan, X.; Zhao, T.S. Role of Phosphorus in Nitrogen, Phosphorus Dual-Doped Ordered Mesoporous Carbon Electrocatalyst for Oxygen Reduction Reaction in Alkaline Media. *Int. J. Hydrogen Energy* **2018**, 43, 1470–1478, doi:10.1016/j.ijhydene.2017.11.165.
- 28. Yang, Q.; Xiao, Z.; Kong, D.; Zhang, T.; Duan, X.; Zhou, S.; Niu, Y.; Shen, Y.; Sun, H.; Wang, S.; et al. New Insight to the Role of Edges and Heteroatoms in Nanocarbons for Oxygen Reduction Reaction. *Nano Energy* **2019**, *66*, 104096, doi:10.1016/j.nanoen.2019.104096.
- 29. Wang, J.; Wu, Z.; Han, L.; Lin, R.; Xiao, W.; Xuan, C.; Xin, H.L.; Wang, D. Nitrogen and Sulfur Co-Doping of Partially Exfoliated MWCNTs as 3-D Structured Electrocatalysts for the Oxygen Reduction Reaction. *J. Mater. Chem. A* **2016**, *4*, 5678–5684, doi:10.1039/C6TA00490C.
- 30. Khan, Z.; Park, S.O.; Yang, J.; Park, S.; Shanker, R.; Song, H.-K.; Kim, Y.; Kwak, S.K.; Ko, H. Binary N,S-Doped Carbon Nanospheres from Bio-Inspired Artificial Melanosomes: A Route to Efficient Air Electrodes for Seawater Batteries. *J. Mater. Chem. A* **2018**, *6*, 24459–24467, doi:10.1039/C8TA10327E.
- 31. Li, Y.; Yang, J.; Huang, J.; Zhou, Y.; Xu, K.; Zhao, N.; Cheng, X. Soft Template-Assisted Method for Synthesis of Nitrogen and Sulfur Co-Doped Three-Dimensional Reduced Graphene Oxide as an Efficient Metal Free Catalyst for Oxygen Reduction Reaction. *Carbon* 2017, 122, 237–246, doi:10.1016/j.carbon.2017.06.046.
- 32. Zhai, C.; Sun, M.; Zhu, M.; Song, S.; Jiang, S. A New Method to Synthesize Sulfur-Doped Graphene as Effective Metal-Free Electrocatalyst for Oxygen Reduction Reaction. *Appl. Surf. Sci.* **2017**, 407, 503–508, doi:10.1016/j.apsusc.2017.02.191.
- 33. Zehtab Yazdi, A.; Roberts, E.P.L.; Sundararaj, U. Nitrogen/Sulfur Co-Doped Helical Graphene Nanoribbons for Efficient Oxygen Reduction in Alkaline and Acidic Electrolytes. *Carbon* **2016**, *100*, 99–108, doi:10.1016/j.carbon.2015.12.096.
- 34. Wang, J.; Wu, Z.-X.; Han, L.-L.; Liu, Y.-Y.; Guo, J.-P.; Xin, H.L.; Wang, D.-L. Rational Design of Three-Dimensional Nitrogen and Phosphorus Co-Doped Graphene Nanoribbons/CNTs Composite for the Oxygen Reduction. *Chinese Chem. Lett.* **2016**, 27, 597–601, doi:10.1016/j.cclet.2016.03.011.
- 35. Sibul, R.; Kibena-Põldsepp, E.; Mäeorg, U.; Merisalu, M.; Kikas, A.; Kisand, V.; Treshchalov, A.; Sammelselg, V.; Tammeveski, K. Sulphur and Nitrogen Co-Doped Graphene-Based Electrocatalysts for Oxygen Reduction Reaction in Alkaline Medium. *Electrochem. commun.* **2019**, 109, 106603, doi:10.1016/j.elecom.2019.106603.
- 36. Palm, I.; Kibena-Põldsepp, E.; Mäeorg, U.; Kozlova, J.; Käärik, M.; Kikas, A.; Leis, J.; Kisand, V.; Tamm, A.; Tammeveski, K. Silicon Carbide-Derived Carbon Electrocatalysts Dual Doped with Nitrogen and Phosphorus for the Oxygen Reduction Reaction in an Alkaline Medium. *Electrochem. commun.* **2021**, 125, 106976, doi:10.1016/j.elecom.2021.106976.
- 37. Palm, I.; Kibena-Põldsepp, E.; Mooste, M.; Kozlova, J.; Käärik, M.; Kikas, A.; Treshchalov, A.; Leis, J.; Kisand, V.; Tamm, A.; et al. Nitrogen and Phosphorus Dual-Doped Silicon Carbide-Derived Carbon/Carbon Nanotube Composite for the Anion-Exchange Membrane Fuel Cell Cathode. *ACS Appl. Energy Mater.* 2022, *5*, 2949–2958, doi:10.1021/acsaem.1c03627.
- 38. Boruah, T.; Das, S.K.; Kumar, G.; Mondal, S.; Dey, R.S. Dual Active Sites in a Triazine-Based Covalent Organic Polymeric Framework Promoting Oxygen Reduction Reaction. *Chem. Commun.* **2022**, *58*, 5506–5509, doi:10.1039/D2CC00865C.
- 39. Mohmad, G.; Sarkar, S.; Biswas, A.; Roy, K.; Dey, R.S. Polymer-Assisted Electrophoretic Synthesis of N-Doped Graphene-Polypyrrole Demonstrating Oxygen Reduction with Excellent Methanol Crossover Impact and Durability. *Chem. A Eur. J.* **2020**, *26*, 12664–12673, doi:10.1002/chem.202002526.
- Sarkar, S.; Biswas, A.; Kamboj, N.; Dey, R.S. Unveiling the Potential of an Fe Bis(Terpyridine) Complex for Precise Development of an Fe-N-C Electrocatalyst to Promote the Oxygen Reduction Reaction. *Inorg. Chem.* 2020, 59, 13453–13464, doi:10.1021/acs.inorgchem.0c01879.
- 41. Colthup, N. B.; Daly, L. H.; Wiberley, S.E. *Introduction to Infrared and Raman Spectroscopy*; 3rd edn.; Academic Press, Inc., 1990; ISBN 0-12-182554-X.
- 42. Silverstein, R.M.; Webster, F.X.; Kiemle, D.J. Spectrometric Identification of Organic Compounds; 7th edn.; John Wiley & Sons. Inc., 2005; ISBN 0-471-39362-2.
- 43. Wu, J.-B.; Lin, M.-L.; Cong, X.; Liu, H.-N.; Tan, P.-H. Raman Spectroscopy of Graphene-Based Materials and Its Applications in Related Devices. *Chem. Soc. Rev.* **2018**, 47, 1822–1873, doi:10.1039/C6CS00915H.
- 44. Schwab, M.G.; Narita, A.; Hernandez, Y.; Balandina, T.; Mali, K.S.; De Feyter, S.; Feng, X.; Müllen, K. Structurally Defined Graphene Nanoribbons with High Lateral Extension. *J. Am. Chem. Soc.* **2012**, *134*, 18169–18172, doi:10.1021/ja307697j.
- 45. Li, X.; Li, T.; Zhong, Q.; Du, K.; Li, H.; Huang, J. Chemical Unzipping of Multiwalled Carbon Nanotubes for High-Capacity Lithium Storage. *Electrochim. Acta* **2014**, *125*, 170–175, doi:10.1016/j.electacta.2014.01.106.
- 46. Wei, R.; Gu, Y.; Zou, L.; Xi, B.; Zhao, Y.; Ma, Y.; Qian, Y.; Xiong, S.; Xu, Q. Nanoribbon Superstructures of Graphene Nanocages for Efficient Electrocatalytic Hydrogen Evolution. *Nano Lett.* **2020**, *20*, 7342–7349, doi:10.1021/acs.nanolett.0c02766.

- 47. Abbas, A.N.; Liu, G.; Narita, A.; Orosco, M.; Feng, X.; Müllen, K.; Zhou, C. Deposition, Characterization, and Thin-Film-Based Chemical Sensing of Ultra-Long Chemically Synthesized Graphene Nanoribbons. *J. Am. Chem. Soc.* **2014**, 136, 7555–7558, doi:10.1021/ja502764d.
- 48. Schwab, M.G.; Narita, A.; Osella, S.; Hu, Y.; Maghsoumi, A.; Mavrinsky, A.; Pisula, W.; Castiglioni, C.; Tommasini, M.; Beljonne, D.; et al. Bottom-Up Synthesis of Necklace-Like Graphene Nanoribbons. *Chem. An Asian J.* **2015**, *10*, 2134–2138, doi:10.1002/asia.201500450.
- 49. Wang, X.; Ma, J.; Zheng, W.; Osella, S.; Arisnabarreta, N.; Droste, J.; Serra, G.; Ivasenko, O.; Lucotti, A.; Beljonne, D.; et al. Cove-Edged Graphene Nanoribbons with Incorporation of Periodic Zigzag-Edge Segments. J. Am. Chem. Soc. 2022, 144, 228–235, doi:10.1021/jacs.1c09000.
- 50. Narita, A.; Feng, X.; Hernandez, Y.; Jensen, S.A.; Bonn, M.; Yang, H.; Verzhbitskiy, I.A.; Casiraghi, C.; Hansen, M.R.; Koch, A.H.R.; et al. Synthesis of Structurally Well-Defined and Liquid-Phase-Processable Graphene Nanoribbons. *Nat. Chem.* **2014**, *6*, 126–132, doi:10.1038/nchem.1819.
- 51. Dresselhaus, M.S.; Jorio, A.; Hofmann, M.; Dresselhaus, G.; Saito, R. Perspectives on Carbon Nanotubes and Graphene Raman Spectroscopy. *Nano Lett.* **2010**, *10*, 751–758, doi:10.1021/nl904286r.
- 52. Gopalsamy, K.; Balamurugan, J.; Thanh, T.D.; Kim, N.H.; Lee, J.H. Fabrication of Nitrogen and Sulfur Co-Doped Graphene Nanoribbons with Porous Architecture for High-Performance Supercapacitors. *Chem. Eng. J.* **2017**, *312*, 180–190, doi:10.1016/j.cej.2016.11.130.
- 53. Boone, C. V.; Maia, G. Pt-Pd and Pt-Pd-(Cu or Fe or Co)/Graphene Nanoribbon Nanocomposites as Efficient Catalysts toward the Oxygen Reduction Reaction. *Electrochim. Acta* **2017**, 247, 19–29, doi:10.1016/j.electacta.2017.06.160.
- 54. Boone, C. V.; Maia, G. Lowering Metal Loadings onto Pt–Pd–Cu/Graphene Nanoribbon Nanocomposites Affects Electrode Collection Efficiency and Oxygen Reduction Reaction Performance. *Electrochim. Acta* **2019**, *303*, 192–203, doi:10.1016/j.electacta.2019.02.079.
- 55. Souza, A.S.; Bezerra, L.S.; Cardoso, E.S.F.; Fortunato, G. V.; Maia, G. Nickel Pyrophosphate Combined with Graphene Nanoribbon Used as Efficient Catalyst for OER. *J. Mater. Chem. A* **2021**, *9*, 11255–11267, doi:10.1039/D1TA00817J.
- 56. Martini, B.K.; Maia, G. Using a Combination of Co, Mo, and Pt Oxides along with Graphene Nanoribbon and MoSe2 as Efficient Catalysts for OER and HER. *Electrochim. Acta* **2021**, 138907, doi:10.1016/j.electacta.2021.138907.
- 57. Cardoso, E.S.F.; Fortunato, G. V; Palm, I.; Kibena-Põldsepp, E.; Greco, A.S.; Júnior, J.L.R.; Kikas, A.; Merisalu, M.; Kisand, V.; Sammelselg, V.; et al. Effects of N and O Groups for Oxygen Reduction Reaction on One- and Two-Dimensional Carbonaceous Materials. *Electrochim. Acta* **2020**, 344, 136052, doi:10.1016/j.electacta.2020.136052.
- 58. Fortunato, G. V.; Cardoso, E.S.F.; Martini, B.K.; Maia, G. Ti/Pt-Pd-Based Nanocomposite: Effects of Metal Oxides on the Oxygen Reduction Reaction. *ChemElectroChem* **2020**, 7, 1610–1618, doi:10.1002/celc.202000268.
- 59. Wilson, N.R.; Pandey, P.A.; Beanland, R.; Rourke, J.P.; Lupo, U.; Rowlands, G.; Römer, R.A. On the Structure and Topography of Free-Standing Chemically Modified Graphene. *New J. Phys.* **2010**, *12*, 125010, doi:10.1088/1367-2630/12/12/125010.
- 60. Han, G.-F.; Li, F.; Zou, W.; Karamad, M.; Jeon, J.-P.; Kim, S.-W.; Kim, S.-J.; Bu, Y.; Fu, Z.; Lu, Y.; et al. Building and Identifying Highly Active Oxygenated Groups in Carbon Materials for Oxygen Reduction to H2O2. *Nat. Commun.* **2020**, *11*, 2209, doi:10.1038/s41467-020-15782-z.
- 61. Jiang, Y.; Liu, J. Definitions of Pseudocapacitive Materials: A Brief Review. *Energy Environ. Mater.* **2019**, 2, 30–37, doi:10.1002/eem2.12028.
- 62. Yang, S.; Verdaguer-Casadevall, A.; Arnarson, L.; Silvioli, L.; Čolić, V.; Frydendal, R.; Rossmeisl, J.; Chorkendorff, I.; Stephens, I.E.L. Toward the Decentralized Electrochemical Production of H2O2: A Focus on the Catalysis. *ACS Catal.* **2018**, *8*, 4064–4081, doi:10.1021/acscatal.8b00217.
- 63. Majumdar, D. Recent Progress in Copper Sulfide Based Nanomaterials for High Energy Supercapacitor Applications. *J. Electroanal. Chem.* **2021**, *880*, 114825, doi:https://doi.org/10.1016/j.jelechem.2020.114825.
- 64. Duraivel, M.; Nagappan, S.; Balamuralitharan, B.; Selvam, S.; Karthick, S.N.; Prabakar, K.; Ha, C.-S.; Kim, H.-J. Superior One-Pot Synthesis of a Doped Graphene Oxide Electrode for a High Power Density Supercapacitor. *New J. Chem.* **2018**, 42, 11093–11101, doi:10.1039/C8NJ01672K.
- 65. Iqbal, M.Z.; Zakar, S.; Haider, S.S. Role of Aqueous Electrolytes on the Performance of Electrochemical Energy Storage Device. *J. Electroanal. Chem.* **2020**, 858, 113793, doi:https://doi.org/10.1016/j.jelechem.2019.113793.
- 66. McCrory, C.C.L.; Jung, S.; Peters, J.C.; Jaramillo, T.F. Benchmarking Heterogeneous Electrocatalysts for the Oxygen Evolution Reaction. *J. Am. Chem. Soc.* **2013**, *135*, 16977–16987, doi:10.1021/ja407115p.
- 67. Fortunato, G. V.; De Lima, F.; Maia, G. Oxygen-Reduction Reaction Strongly Electrocatalyzed by Pt Electrodeposited onto Graphene or Graphene Nanoribbons. *J. Power Sources* **2016**, 302, 247–258, doi:10.1016/j.jpowsour.2015.10.069.

- 68. Wierzbicki, S.; Darvishzad, T.; Gryboś, J.; Stelmachowski, P.; Sojka, Z.; Kruczała, K. Switching the Locus of Oxygen Reduction and Evolution Reactions between Spinel Active Phase and Carbon Carrier upon Heteroatoms Doping. *Catal. Today* **2023**, *418*, 114043, doi:10.1016/j.cattod.2023.114043.
- 69. Chai, G.-L.; Hou, Z.; Ikeda, T.; Terakura, K. Two-Electron Oxygen Reduction on Carbon Materials Catalysts: Mechanisms and Active Sites. *J. Phys. Chem. C* **2017**, 121, 14524–14533, doi:10.1021/acs.jpcc.7b04959.
- 70. Li, L.; Tang, C.; Zheng, Y.; Xia, B.; Zhou, X.; Xu, H.; Qiao, S. Tailoring Selectivity of Electrochemical Hydrogen Peroxide Generation by Tunable Pyrrolic-Nitrogen-Carbon. *Adv. Energy Mater.* **2020**, *10*, 2000789, doi:10.1002/aenm.202000789.
- 71. Xia, Y.; Zhao, X.; Xia, C.; Wu, Z.-Y.; Zhu, P.; Kim, J.Y.; Bai, X.; Gao, G.; Hu, Y.; Zhong, J.; et al. Highly Active and Selective Oxygen Reduction to H2O2 on Boron-Doped Carbon for High Production Rates. *Nat. Commun.* **2021**, *12*, 4225, doi:10.1038/s41467-021-24329-9.
- 72. Perazzolo, V.; Durante, C.; Pilot, R.; Paduano, A.; Zheng, J.; Rizzi, G.A.; Martucci, A.; Granozzi, G.; Gennaro, A. Nitrogen and Sulfur Doped Mesoporous Carbon as Metal-Free Electrocatalysts for the in Situ Production of Hydrogen Peroxide. *Carbon* 2015, 95, 949–963, doi:10.1016/j.carbon.2015.09.002.
- 73. Qin, M.; Fan, S.; Wang, L.; Gan, G.; Wang, X.; Cheng, J.; Hao, Z.; Li, X. Oxygen and Nitrogen Co-Doped Ordered Mesoporous Carbon Materials Enhanced the Electrochemical Selectivity of O2 Reduction to H2O2. *J. Colloid Interface Sci.* **2020**, *562*, 540–549, doi:10.1016/j.jcis.2019.11.080.
- 74. Gao, Y.; Wang, Q.; Ji, G.; Li, A.; Niu, J. Doping Strategy, Properties and Application of Heteroatom-Doped Ordered Mesoporous Carbon. *RSC Adv.* **2021**, *11*, 5361–5383, doi:10.1039/D0RA08993A.
- 75. Wang, X.; Liu, R.; Waje, M.M.; Chen, Z.; Yan, Y.; Bozhilov, K.N.; Feng, P. Sulfonated Ordered Mesoporous Carbon as a Stable and Highly Active Protonic Acid Catalyst. *Chem. Mater.* **2007**, *19*, 2395–2397, doi:10.1021/cm070278r.
- 76. Xie, L.; Wang, P.; Li, Y.; Zhang, D.; Shang, D.; Zheng, W.; Xia, Y.; Zhan, S.; Hu, W. Pauling-Type Adsorption of O2 Induced Electrocatalytic Singlet Oxygen Production on N–CuO for Organic Pollutants Degradation. *Nat. Commun.* **2022**, *13*, 5560, doi:10.1038/s41467-022-33149-4.
- 77. Schürmann, A.; Luerßen, B.; Mollenhauer, D.; Janek, J.; Schröder, D. Singlet Oxygen in Electrochemical Cells: A Critical Review of Literature and Theory. *Chem. Rev.* **2021**, 121, 12445–12464, doi:10.1021/acs.chemrev.1c00139.

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.